

Project _____

Type _____

Notes _____

Quantity _____

Date _____

GENERAL

Ceiling _____

Suspended _____

Cement Grey + White Matt _____

IP20 _____

Interior _____

525 lm _____

LED

1800 K - 2850 K _____

3-step binning _____

ELECTRICAL

phase-cut dim _____

220 - 240 V _____

Total connected power 12.0 W _____

Class 2 _____

Safety distance 0.3 m _____


PHYSICAL

Diameter 760 mm _____


Height 235 mm _____

2.3 kg _____

incl. 4.0 m suspension _____



Cone shaped ceiling suspended luminaire made from aluminium; surface Cement Grey + White Matt wet painted; matt texture; inclusive black adjustable cable suspension max. 4000mm; PCB 3-step binning; phase-cut dim; light colour 1800 K - 2850 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; PC2; ceiling base not included; light source replaceable by an authorized professional;



Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.97	0.93	0.89	0.85	0.81
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to “CIE 97, Maintenance of indoor electric lighting systems”, 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

MOUNTING

Invisible ceiling base

COLOUR	L · W (MM)	ORDERCODE
Black	140 · 66	9 0 0 1 5 1 9 5
White	140 · 66	9 0 0 1 5 1 9 6



Single base

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
ceiling base round	Black	Ø 84 · 29	9 0 0 5 2 0 2 1
ceiling base round	White	Ø 84 · 29	9 0 0 5 2 0 2 2

Semi recessed base

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
for shades without steel wire only	White	Ø 84 · 72	9 0 0 5 2 0 2 6
for shades without steel wire only	Black	Ø 84 · 72	9 0 0 5 2 0 2 7